

Declaration of performance**No. 001DoP-3mm-170215**

1. **Unique identification code of the product type:** Dry-pressed ceramic tiles with water absorption $E_b \leq 0,5\%$; nominal thickness 3 mm.
2. **Intended uses:** For internal and external walls.
3. **Manufacturer:** Laminam S.p.A. via Ghiarola Nuova, 258 – 41042 Fiorano Modenese (MO) – Italy.
4. **System of AVCP:** System 4.
5. **Harmonized standard:** EN 14411:2016
6. **Declared performances:**

<u>Essential characteristics</u>	<u>Performance</u>
Name	Laminam 3
Reaction to fire	A1
Release of dangerous substance, for:	
– Cadmium	NPD
– Lead	NPD
Bond strength/adhesion, for:	
Cementitious adhesive, type C2S1/C2S2	1 N/mm ²
Thermal shock resistance	Pass
Durability for:	
– Internal use	Pass
– External use: freeze-thaw resistance	Pass

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Roberto Pederzoli, Quality Manager

Fiorano Modenese, 15 February 2017

